

Льдогенераторы хлопьевидного льда АГ

Технические характеристики

По вопросам продаж и поддержки обращайтесь:

Алматы (727)345-47-04
Ангарск (3955)60-70-56
Архангельск (8182)63-90-72
Астрахань (8512)99-46-04
Барнаул (3852)73-04-60
Белгород (4722)40-23-64
Благовещенск (4162)22-76-07
Брянск (4832)59-03-52
Владивосток (423)249-28-31
Владикавказ (8672)28-90-48
Владимир (4922)49-43-18
Волгоград (844)278-03-48
Вологда (8172)26-41-59
Воронеж (473)204-51-73
Екатеринбург (343)384-55-89

Иваново (4932)77-34-06
Ижевск (3412)26-03-58
Иркутск (395)279-98-46
Казань (843)206-01-48
Калининград (4012)72-03-81
Калуга (4842)92-23-67
Кемерово (3842)65-04-62
Киров (8332)68-02-04
Коломна (4966)23-41-49
Кострома (4942)77-07-48
Краснодар (861)203-40-90
Красноярск (391)204-63-61
Курск (4712)77-13-04
Курган (3522)50-90-47
Липецк (4742)52-20-81

Магнитогорск (3519)55-03-13
Москва (495)268-04-70
Мурманск (8152)59-64-93
Набережные Челны (8552)20-53-41
Нижний Новгород (831)429-08-12
Новокузнецк (3843)20-46-81
Ноябрьск (3496)41-32-12
Новосибирск (383)227-86-73
Омск (3812)21-46-40
Орел (4862)44-53-42
Оренбург (3532)37-68-04
Пенза (8412)22-31-16
Петрозаводск (8142)55-98-37
Псков (8112)59-10-37
Пермь (342)205-81-47

Ростов-на-Дону (863)308-18-15
Рязань (4912)46-61-64
Самара (846)206-03-16
Санкт-Петербург (812)309-46-40
Саратов (845)249-38-78
Севастополь (8692)22-31-93
Саранск (8342)22-96-24
Симферополь (3652)67-13-56
Смоленск (4812)29-41-54
Сочи (862)225-72-31
Ставрополь (8652)20-65-13
Сургут (3462)77-98-35
Сыктывкар (8212)25-95-17
Тамбов (4752)50-40-97
Тверь (4822)63-31-35

Тольятти (8482)63-91-07
Томск (3822)98-41-53
Тула (4872)33-79-87
Тюмень (3452)66-21-18
Ульяновск (8422)24-23-59
Улан-Удэ (3012)59-97-51
Уфа (347)229-48-12
Хабаровск (4212)92-98-04
Чебоксары (8352)28-53-07
Челябинск (351)202-03-61
Череповец (8202)49-02-64
Чита (3022)38-34-83
Якутск (4112)23-90-97
Ярославль (4852)69-52-93

Россия +7(495)268-04-70

Казахстан +7(727)345-47-04

Беларусь +(375)257-127-884

Узбекистан +998(71)205-18-59

Киргизия +996(312)96-26-47

эл.почта: hib@nt-rt.ru || сайт: <https://hibu.nt-rt.ru/>

AF 87 XSafe EcoX


Self Contained Ice Machine 70 kg

		FEATURES • Produces granular shape ice flakes, 75% hardness • Electronically controlled operation, with self-diagnostic functions with external alarm lights providing operational information for early alert and fast diagnosis of operating issues • External Components constructed from corrosion-resistant stainless steel crafted for optimal aesthetic appeal through superior fit and finish • Ergonomically convenient, slanted & disappearing storage bin door • Front access for easier maintenance • Front-in, front-out airflow allows for built-in installations • Also available as AF87 LAB: specifically designed to be used with demineralized and distilled water. Already fitted with Shuko plug. • XSafe: natural sanitation system, integrated inside the ice maker and operating automatically 24/7 to keep equipment clean & safe.	
 AF 87 Flake ice Residual water content 25%	CONDENSING SYSTEM Air cooled	INTERNAL BIN CAPACITY 25 kg	
	REFRIGERANT GAS R290		
	VOLTAGE V/Hz/ph 230/50/1		
		OPERATING REQUIREMENTS	
			MinimumMaximum
		Air temperature	1043
		Water temperature	538
		Water pressure	1 bar (14 psi)5 bar (70 psi)
		Electrical voltage	-10%+10%

Self Contained Ice Machine 70 kg

AF 87 *XSafe*

Self Contained Ice Machine 70 kg



UNIT DATA				SHIPPING DATA							
Size (W x D x H)		535 x 620 x 890 mm		Carton (W x D x H)		600 x 690 x 980 mm					
Net weight		50 kg		Weight		58 kg					
		24 h ice production kg °C Amb. / °C Water			Energy consumption (*)		Water usage (*)	Instant power	Compressor	Circuit wires	Max. fuse size
Version	Voltage	10°C/10°C kg	21°C/10°C kg	32°C/21°C kg	kWh/ 100 kg	kWh/ 24h	l/h	W	W	No. x Ømm²	A
AF 87 AS	230/50/1	70	68	56	10.6	6.2	2.4	275	200	3 x 1.5	10

(*) Data refer to 32°C Amb. / 21°C Water temperature conditions

AF 107 EcoX XSafe





Self Contained Ice Machine 130 kg

		FEATURES • Produces granular shape ice flakes, 75% hardness. • Electronically controlled operation, with self-diagnostic functions with external alarm lights providing operational information for early alert and fast diagnosis of operating issues. • External Components constructed from corrosion-resistant stainless steel crafted for optimal aesthetic appeal through superior fit and finish. • Ergonomically convenient, slanted & disappearing storage bin door. • Front access for easier maintenance. • Front-in, front-out airflow allows for built-in installations. • XSafe: natural sanitation system, integrated inside the ice maker and operating automatically 24/7 to keep equipment clean & safe.	
 AF 107 Flake ice Residual water content 25%	CONDENSING SYSTEM Air cooled	INTERNAL BIN CAPACITY 30 kg	
	REFRIGERANT GAS R290		
	VOLTAGE V/Hz/ph 230/50/1		
		OPERATING REQUIREMENTS	
			MinimumMaximum
		Air temperature	1043
		Water temperature	538
		Water pressure	1 bar (14 psi)5 bar (70 psi)
		Electrical voltage	-10%+10%

Self Contained Ice Machine 130 kg


AF 107 XSafe

Self Contained Ice Machine 130 kg



UNIT OF MEASUREMENT: mm

1. 13/16" OD - OVERFLOW DRAIN
2. 3/4" GAS - WATER INLET
3. 3/4" GAS - WATER OUTLET
WATER COOLED UNIT ONLY
4. 3/4" GAS - WATER INLET
WATER COOLED UNIT ONLY
5. CORD SET



UNIT DATA				SHIPPING DATA							
Size (W x D x H)		592 x 622 x 1078 mm		Carton (W x D x H)		670 x 690 x 1180 mm					
Net weight		66 kg		Weight		74 kg					
		24 h ice production kg °C Amb. / °C Water			Energy consumption (*)		Water usage (*)	Instant power	Compressor	Circuit wires	Max. fuse size
Version	Voltage	10°C/10°C	21°C/10°C	32°C/21°C	kWh/ 100 kg	kWh/ 24h	l/h	W	W	No. x Ømm²	A
		kg	kg	kg							
AF 107 AS	230/50/1	130	126	102	8.4	9	4.5	400	1000	3 x 1.5	10

(*) Data refer to 32°C Amb. / 21°C Water temperature conditions

AF 127 EcoX XSafe


Self Contained Ice Machine 126 kg

		FEATURES • Produces granular shape ice flakes, 75% hardness. Ice scoop holder safely positioned in ice-storage bin. • Resistant stainless steel exterior. • Advanced diagnostics computerized control. • Front panel in & out airflow (air-cooled model only) for built-in installation. • Front access condenser air filter, removable and washable (air cooled version). • Easily accessible, front panel mount, ON-OFF Switch. • Easy, front panel access to technical / service area of the machine. Routine maintenance visible alarm light on front panel. • Ergonomically designed ice storage access, with disappearing door. Door-closing movement dampening system. • XSafe: natural sanitation system, integrated inside the ice maker and operating automatically 24/7 to keep equipment clean & safe.	
 AF 127 Flake ice Residual water content 25%	CONDENSING SYSTEM Air cooled	INTERNAL BIN CAPACITY 40 kg	
	REFRIGERANT GAS R290		
	VOLTAGE V/Hz/ph 230/50/1		
		OPERATING REQUIREMENTS	
			MinimumMaximum
		Air temperature	1043
		Water temperature	538
		Water pressure	1 bar (14 psi)5 bar (70 psi)
		Electrical voltage	-10%+10%

Self Contained Ice Machine 126 kg

AF 127 EcoX XSafe

Self Contained Ice Machine 126 kg



UNIT DATA					SHIPPING DATA						
Size (W x D x H)		950 x 605 x 872 mm			Carton (W x D x H)		1030 x 680 x 960 mm				
Net weight		66 kg			Weight		77 kg				
		24 h ice production kg °C Amb. / °C Water			Energy consumption (*)		Water usage (*)	Instant power	Compressor	Circuit wires	Max. fuse size
Version	Voltage	10°C/10°C	21°C/10°C	32°C/21°C	kWh/ 100 kg	kWh/ 24h	l/h	W	W	No. x Ømm²	A
		kg	kg	kg							
AF 127 AS	230/50/1	126	121	94	9.6	9.6	4.1	450	1000	3 x 1.5	10

(*) Data refer to 32°C Amb. / 21°C Water temperature conditions

Алматы (727)345-47-04
Ангарск (3955)60-70-56
Архангельск (8182)63-90-72
Астрахань (8512)99-46-04
Барнаул (3852)73-04-60
Белгород (4722)40-23-64
Благовещенск (4162)22-76-07
Брянск (4832)59-03-52
Владивосток (423)249-28-31
Владикавказ (8672)28-90-48
Владимир (4922)49-43-18
Волгоград (844)278-03-48
Вологда (8172)26-41-59
Воронеж (473)204-51-73
Екатеринбург (343)384-55-89

Иваново (4932)77-34-06
Ижевск (3412)26-03-58
Иркутск (395)279-98-46
Казань (843)206-01-48
Калининград (4012)72-03-81
Калуга (4842)92-23-67
Кемерово (3842)65-04-62
Киров (8332)68-02-04
Коломна (4966)23-41-49
Кострома (4942)77-07-48
Краснодар (861)203-40-90
Красноярск (391)204-63-61
Курск (4712)77-13-04
Курган (3522)50-90-47
Липецк (4742)52-20-81

Магнитогорск (3519)55-03-13
Москва (495)268-04-70
Мурманск (8152)59-64-93
Набережные Челны (8552)20-53-41
Нижний Новгород (831)429-08-12
Новокузнецк (3843)20-46-81
Ноябрьск (3496)41-32-12
Новосибирск (383)227-86-73
Омск (3812)21-46-40
Орел (4862)44-53-42
Оренбург (3532)37-68-04
Пенза (8412)22-31-16
Петрозаводск (8142)55-98-37
Псков (8112)59-10-37
Пермь (342)205-81-47

Ростов-на-Дону (863)308-18-15
Рязань (4912)46-61-64
Самара (846)206-03-16
Санкт-Петербург (812)309-46-40
Саратов (845)249-38-78
Севастополь (8692)22-31-93
Саранск (8342)22-96-24
Симферополь (3652)67-13-56
Смоленск (4812)29-41-54
Сочи (862)225-72-31
Ставрополь (8652)20-65-13
Сургут (3462)77-98-35
Сыктывкар (8212)25-95-17
Тамбов (4752)50-40-97
Тверь (4822)63-31-35

Тольятти (8482)63-91-07
Томск (3822)98-41-53
Тула (4872)33-79-87
Тюмень (3452)66-21-18
Ульяновск (8422)24-23-59
Улан-Удэ (3012)59-97-51
Уфа (347)229-48-12
Хабаровск (4212)92-98-04
Чебоксары (8352)28-53-07
Челябинск (351)202-03-61
Череповец (8202)49-02-64
Чита (3022)38-34-83
Якутск (4112)23-90-97
Ярославль (4852)69-52-93

Россия +7(495)268-04-70

Казахстан +7(727)345-47-04

Беларусь +(375)257-127-884

Узбекистан +998(71)205-18-59

Киргизия +996(312)96-26-47

По вопросам продаж и поддержки обращайтесь:

эл.почта: hib@nt-rt.ru || сайт: <https://hibu.nt-rt.ru/>